

detecting a need for assisting the user with input for a source code module under development;

determining a current cursor position representing a location in the source code module where the user is currently providing input;

determining input items which are suitable for input in the source code module at the current cursor position;

displaying to the user a list of said suitable input items; and

in response to selection by the user of a particular item from the list, automatically completing input at the current cursor position;

wherein said detecting step includes:

determining instances in the source code module where the system can automatically provide input; and

wherein said detecting step includes:

determining in the source code module use of a structure variable which references a nested data member.

8. - 9. --CANCELLED--

²
~~10.~~ (Amended) In a development system, a method for assisting a user with inputting source code for a computer program, the method comprising:

detecting a need for assisting the user with input for a source code module under development;

determining a current cursor position representing a location in the source code module where the user is currently providing input;

determining input items which are suitable for input in the source code module at the current cursor position;

displaying to the user a list of said suitable input items; and

in response to selection by the user of a particular item from the list, automatically completing input at the current cursor position;

C2 wherein said current cursor position comprises a line number and a column position for a particular source code file.

[11. --CANCELLED--

C3 ⁴
~~13.~~ (Amended) In a development system, a method for assisting a user with inputting source code for a computer program, the method comprising:
detecting a need for assisting the user with input for a source code module under development;
determining a current cursor position representing a location in the source code module where the user is currently providing input;
determining input items which are suitable for input in the source code module at the current cursor position;
displaying to the user a list of said suitable input items; and
in response to selection by the user of a particular item from the list, automatically completing input at the current cursor position;
wherein said step of determining input items which are suitable for input in the source code module includes:
determining which variables are within scope for the current cursor position; and
eliminating as a suitable input item any item that is not within scope for the current cursor position; and
wherein said step of compiling the source code module up to the current cursor position includes:
skipping compilation of any method defined in the source code unless the cursor is currently positioned within the method.

⁵
~~14.~~ (Amended) In a development system, a method for assisting a user with inputting source code for a computer program, the method comprising: